

Appln. No. 09/993,251

Attorney Docket No. 10541-1161

Listing of Claims:

1. (Currently Amended): A method of forming a catalytic converter, the method comprising:

providing a catalytic converter having a central portion and an end portion, wherein the central portion defines a horizontal central axis;

rotating the catalytic converter around the central axis;

placing a roller perpendicular to the central axis;

keeping the roller perpendicular to the central axis;

forming the end portion by moving the roller in a transverse direction with respect to the central axis, wherein moving the roller in a transverse direction with respect to the central axis includes dividing the end portion into multiple imaginary planes perpendicular to the central axis, forming a contour corresponding to the multiple imaginary planes, and programming the roller to follow the contour; and

forming the end portion by moving the roller in a parallel direction with respect to the central axis.

2. (Cancelled)

3. (Original): The method of claim 1, wherein the end portion defines an axis at an angle with respect to the central axis of the catalytic converter.

4. (Original): The method of claim 3, wherein the angle between the axis of the end portion and the central axis is in the range of 30 to 60 .

5. (Cancelled)

6. (Original): The method of claim 1, further comprising rotating the roller around an axis parallel to the central axis.

7. (Original): The method of claim 1, wherein the step of placing the roller comprises the step of contacting a surface of the catalytic converter such that

-2-

BRINKS
HOFFER
GILSON
LIONE

BRINKS HOFER GILSON & LIONE
PO Box 10395
Chicago, IL 60611-5599

Appln. No. 09/993,251

Attorney Docket No. 10541-1161

moving the roller in the transverse direction reduces the diameter of the catalytic converter at the surface.

8. (Original): The method of claim 1, wherein forming the end portion further comprises cutting an end part of the end portion such that the end part is angled with respect to a vertical axis of the catalytic converter.

9. (Currently Amended): A method of forming an end portion of a catalytic converter, the method comprising:

providing a catalytic converter having a central portion and an end portion such that the central portion defines a horizontal central axis;

rotating the catalytic converter around the central axis;

placing a roller perpendicular to the central axis;

keeping the roller perpendicular to the central axis;

moving the roller in a transverse direction with respect to the central axis, wherein moving the roller in the transverse direction includes dividing the end portion into multiple imaginary planes perpendicular to the central axis, forming a contour corresponding to the multiple imaginary planes, and programming the roller to follow the contour, wherein the end portion defines an axis at an angle with respect to the central axis; and

moving the roller in a parallel direction with respect to the central axis.

10. (Cancelled)

11. (Original): The method of claim 9, wherein the angle between the axis of the end portion and the central axis is in the range of 30 to 60 .

12. (Cancelled)

13. (Original): The method of claim 9, rotating the roller around an axis perpendicular to the central axis.

-3-

BRINKS
HOFER
GILSON
& LIONE

BRINKS HOFER GILSON & LIONE
PO Box 10395
Chicago, IL 60611-5599

Appln. No. 09/993,251

Attorney Docket No. 10541-1161

14. (Original): The method of claim 9, wherein the step of placing the roller comprises contacting a surface of the catalytic converter such that moving the roller in the transverse direction reduces the diameter of the catalytic converter at the surface.

15. (Original): The method of claim 9, wherein forming the end portion further comprises cutting an end part of said end portion such that the end part is angled with respect to a vertical axis of the catalytic converter.

16. (Currently Amended): A method of forming an oblique end portion of a catalytic converter, the method comprising:

providing a catalytic converter having a central portion and an end portion such that the central portion defines a horizontal central axis;

rotating the catalytic converter around the central axis;

placing one roller perpendicular to the central axis such that the roller contacts a surface of the end portion;

keeping the roller perpendicular to the central axis;

moving the roller in a transverse direction with respect to the central axis and moving the roller in a parallel direction with respect to the central axis, such that the end portion defines an axis at an angle with respect to the central axis, wherein moving the roller in the transverse direction includes dividing the end portion into multiple imaginary planes perpendicular to the central axis, forming a contour corresponding to the multiple imaginary planes, and programming the roller to follow the contour; and

reducing the diameter of the end portion in the surface .

17. (Original): The method of Claim 16, wherein the angle between the axis of the end portion and the central axis is in the range of 30 to 60 .

18. (Cancelled).

-4-

BRINKS
HOFER
GILSON
ALONE

BRINKS HOFER GILSON & LIONE
PO Box 10395
Chicago, IL 60611-5599

Appln. No. 09/993,251

Attorney Docket No. 10541-1161

19. (Original): The method of claim 16, rotating the roller around an axis perpendicular to the central axis.

20. (Original): The method of claim 16, wherein forming the end portion further comprises cutting an end part of the end portion such that the end part is angled with respect to a vertical axis of the catalytic converter.



BRINKS HOFER GILSON & LIONE
PO Box 10395
Chicago, IL 60611-5599